RITEWAY

LAND ROLLERS



RiteWayMfg.com

THIS IS HOW WE ROLL.






THIS IS WHY WE ROLL.





1 - Large Diameter Drums.

Rite Way land rollers feature a 42” diameter drum with a 0.5” thick drum wall. This large drum has low rolling resistance while applying serious weight to punch rocks into the soil and create a smooth level surface for in-crop machinery operations and rapid unimpeded harvests. A heavier 0.6” drum wall is optional. Farmers in wet regions can order mud scrapers to keep their drums running clean.



2 - Level the field.

No two acres are the same.
Shorter drum sections move independently and cover every inch of your land regardless of topography. Finish rollers keep the soil surface smooth and level while maximizing the main roller’s ability to follow the land.





3 - Safe and Secure Transport.

Our land rollers are heavy machines, so we’ve developed a robust system for keeping your machine safe and secure between fields. Our transport wing locks make a rigid connection between roller sections, and the wing tie bar keeps our land rollers secure and controlled when turning corners. Wing tie bars are standard on five and seven section rollers and optional in three section rollers. Large load carrying tires are the final touch to ensure moving from point a to b is a painless experience.

4 - FORWARD™ Unfold.

Unfolding into field position shouldn’t be a pain in the neck. The Rite Way Land Rollers have hydraulicly pivoting wing tires that allow our machines to unfold while driving forward. Back the machine up a short distance to lock the draft arms and you are ready for work. This unique system allows our land rollers to be pulled behind seeding equipment to optimize farm efficiency.



Easy to transport

F3, F5, and F7 rollers fold to 14 feet wide for easy transport. The F3-NT model folds to a mere 12 feet, making tight quarters and maneuvering a breeze.

BUILT STRONG FOR YOUR TOUGHEST FIELDS.

SPECIFICATIONS:



F-3

MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 0.5" DRUM	WEIGHT 0.6" DRUM
F3-32	**32'** (9.8 m)	**10'-12'-10'** (3.1 m-3.6 m-3.1 m)	**38'** (11.6 m)	**14'** (4.3 m)	**17,640 lbs** (8,100 kg)	19,560 lbs
F3-36	**36'** (11.0 m)	**12'-12'-12'** (3.6 m-3.6 m-3.6 m)	**40'** (12.2 m)	**14'** (4.3 m)	**19,000 lbs** (8,618 kg)	21,160 lbs
F3-42	**42'** (12.8 m)	**15'-12'-15'** (4.5 m-3.6 m-4.5 m)	**45'** (13.7 m)	**14'** (4.3 m)	**21,220 lbs** (9,625 kg)	23,740 lbs
F3-46	**46'** (14.1 m)	**17'-12'-17'** (5.2 m-3.6 m-5.2 m)	**47'** (14.3 m)	**14'** (4.3 m)	**22,910 lbs** (10,391 kg)	25,670 lbs
F3-52	**52'** (15.8 m)	**20'-12'-20'** (6.1 m-3.6 m-6.1 m)	**50'** (15.2 m)	**14'** (4.3 m)	**24,400 lbs** (11,067 kg)	27,520 lbs
F3-40 NT	**40'** (12.2 m)	**15'-10'-15'** (4.5 m-3.1 m-4.5 m)	**45'** (13.7 m)	**12'** (3.7 m)	**20,600 lbs** (9.344 kg)	23,000 lbs
F3-50 NT	**50'** (15.2 m)	**20'-10'-20'** (6.1 m-3.6 m-6.1 m)	**50'** (15.2 m)	**12'** (3.7 m)	**23,100 lbs** (10,478 kg)	26,100 lbs



F-5

MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 0.5" DRUM	WEIGHT 0.6" DRUM
F5-46	**46'** (14 m)	**8'-8'-12'-8'-8'** (2.4 m-2.4 m-3.6 m-2.4 m-2.4 m)	**47' 4"** (14.4 m)	**14'** (4.3 m)	**23,000 lbs** (10,432 kg)	25,640 lbs
F5-50	**50'** (14.4 m)	**10'-8'-12'-8'-10'** (3.1 m-2.4 m-3.6 m-2.4 m-3.1 m)	**49' 4"** (15.0 m)	**14'** (4.3 m)	**24,800 lbs** (11,249 kg)	27,680 lbs
F5-54	**54'** (16.4 m)	**10'-10'-12'-10'-10'** (3.1 m-3.1 m-3.6 m-3.1 m-3.1 m)	**51' 4"** (15.6 m)	**14'** (4.3 m)	**26,490 lbs** (12,016 kg)	29,610 lbs
F5-58	**58'** (17.7 m)	**12'-10'-12'-10'-12'** (3.6 m-3.1 m-3.6 m-3.1 m-3.6 m)	**53' 4"** (16.2 m)	**14'** (4.3 m)	**28,478 lbs** (12,917 kg)	31,838 lbs
F5-62	**62'** (18.9 m)	**12'-12'-12'-12'-12'** (3.6 m-3.6 m-3.6 m-3.6 m-3.6 m)	**55' 4"** (16.9 m)	**14'** (4.3 m)	**30,250 lbs** (13,721 kg)	33,850 lbs
F5-68	**68' 4"** (20.8 m)	**12'-15'-12'-15'-12'** (3.6 m-4.5 m-3.6 m-4.5 m-3.6 m)	**61' 6"** (18.7 m)	**14'** (4.3 m)	**32,620 lbs** (14,796 kg)	36,580 lbs
F5-74	**74'** (22.5 m)	**15'-15'-12'-15'-15'** (4.5 m-4.5 m-3.6 m-4.5 m-4.5 m)	**64' 6"** (19.7 m)	**14'** (4.3 m)	**35,520 lbs** (16,112 kg)	—
F5-78	**78'** (23.7 m)	**17'-15'-12'-15'-17'** (5.2 m-4.5 m-3.6 m-4.5 m-5.2 m)	**66' 6"** (20.3 m)	**14'** (4.3 m)	**37,440 lbs** (16,982 kg)	—
F5-84	**84'** (25.6 m)	**20'-15'-12'-15'-20'** (6.1 m-4.5 m-3.6 m-4.5 m-6.1 m)	**69' 6"** (21.2 m)	**14'** (4.3 m)	**40,320 lbs** (18,289 kg)	—



F-7

MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 0.5" DRUM
F7-65	**65'** (19.8 m)	**8'-8'-8'-12'-8'-8'-8'** (2.4 m-2.4 m-2.4 m-3.6 m-2.4 m-2.4 m-2.4 m)	**59' 8"** (18.2 m)	**14'** (4.3 m)	**32,500 lbs** (32,500 kg)
F7-69	**69'** (21.0 m)	**10'-8'-8'-12'-8'-8'-10'** (3.1 m-2.4 m-2.4 m-3.6 m-2.4 m-2.4 m-3.1 m)	**61' 8"** (18.2 m)	**14'** (4.3 m)	**33,740 lbs** (15,304 kg)
F7-73	**73'** (22.3 m)	**10'-10'-8'-12'-8'-10'-10'** (3.1 m-3.1 m-2.4 m-3.6 m-2.4 m-3.1 m-3.1 m)	**62' 6"** (19.0 m)	**14'** (4.3 m)	**35,040 lbs** (15,894 kg)
F7-77	**77'** (23.5 m)	**12'-10'-8'-12'-8'-10'-12'** (3.6 m-3.1 m-2.4 m-3.6 m-2.4 m-3.1 m-3.6 m)	**65' 8"** (20.0 m)	**14'** (4.3 m)	**36,960 lbs** (16,765 kg)
F7-81	**81'** (26.7 m)	**12'-10'-10'-12'-10'-10'-12'** (3.6 m-3.1 m-3.1 m-3.6 m-3.1 m-3.1 m-3.6 m)	**67' 8"** (20.6 m)	**14'** (4.3 m)	**38,718 lbs** (17,562 kg)
F7-85	**85'** (25.9 m)	**12'-12'-10'-12'-10'-12'-12'** (3.6 m-3.6 m-3.1 m-3.6 m-3.1 m-3.6 m-3.6 m)	**69' 8"** (21.2 m)	**14'** (4.3 m)	**39,950 lbs** (18,121 kg)
F7-89	**89'** (27.1 m)	**12'-12'-12'-12'-12'-12'-12'** (3.6 m-3.6 m-3.6 m-3.6 m-3.6 m-3.6 m-3.6 m)	**71' 8"** (21.8 m)	**14'** (4.3 m)	**41,190 lbs** (18,683 kg)

TIRES

MODEL	MAIN FRAME	WING AXLE
F3 & F5	12.5L x 15-12 ply	12.5L x 15-12 ply
F5 Optional	380/55 R16.5	320/70 R15
F5-62 and larger + F7	380/55 R16.5	12.5L x 15-12 ply
F7 Optional		320/70 R15

**TRUCK TIRES AVAILABLE UPON REQUEST

We are continuously improving our products. Design specifications and material are subject to change without notice.

For more information on the Land Roller, or other land improvement equipment, visit your local Rite Way equipment dealer or visit **www.RiteWayMfg.com**

Toll free: 1-800-352-8822 /RiteWayMfg @RiteWayMfgCo

© Rite Way MFG. CO. LTD.

Printed in Canada

RITEWAY SFE