Power Unit 4100

4100

The Ventrac **4100** is not just any compact tractor. Ventrac's articulating and oscillating frame design gives the operator enhanced maneuverability and stability over traditional tractors by conforming to the contour of the terrain, easily navigating around obstacles. The attachment is placed out front in natural view offering greater precision as well as maximum protection for the operator.

The 4100 is equipped with the **Ventrac Mount System**. Attachments connect in about a minute, all without tools. Over 30 different attachments are available for almost any job. A wide variety of accessories are available to customize your 4100 to better fit your needs.

Operation is easy with Ventrac's patented S.D.L.A. control located next to the operator, controlling Speed, Direction, Lift and Auxiliary function all with one hand. Comfort is not overlooked with standard features such as Comfort Seat, Power Steering, Cup Holder, Storage Box, among other refinements.







Standard Features:

- Air Cooled Engine
- All Wheel Drive
- S.D.L.A. controls Speed, Direction, Lift, and Auxiliary hydraulics from a single point
- Heavy Duty Hydrostatic Drive
- Articulation and Oscillating Frame
- Easy Ventrac Mount System

Optional Accessories:

- Weight Transfer System
- Foot control
- Folding Roll Bar - ROPS
- Rear Weights
- 3-Point Hitch
- Front Fenders
- AND MORE!

VENTRAC® MOUNT SYSTEM

Over 30 Ventrac Mount Attachments

328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Power Unit 4100

4100

Stock Codes	4100
KT4131 (Van. 31hp Gas)	39.51120
Engine	
Briggs & Stratton 31hp gas 2 cyl. (Engine Model 54)	Air Cooled 895 cc
Electrical	
Battery	450 Cold Cranking amp battery
Voltage	12 Volts
Alternator	50 amp
Powertrain	
Hydraulic Pump	Sauer/Danfoss Series 15
Transaxles (connected in series)	Peerless 2600 Dual Range Transaxles (2)
Hydraulic Oil Cooler	Standard
Hydraulic Oil Filters	2 (10 and 25 micron)
Tires	
Standard	Titan HD Fieldtrax (22x12-8 inches) (56x30-20 cm)
Optional Turf Master	Turf Master (22x11-10 inches) (56x28x26 cm)
Optional Bar	Power Trac (21x11-8 inches) (53x28-20 cm)
Instrument Panel	
Standard Indicators	Tachometer/Hourmeter Low Oil Indicator Voltmeter PTO Switch/Indicator Light

Dimensions	4100
Wheelbase	43 Inches (109 cm)
Length	79 inches (201 cm)
Width w/single Fieldtrax tires	48 inches (122 cm)
Width w/dual Fieldtrax tires	70 inches (178 cm)
Width W/single Turf Master Tires	49 inches (124 cm)
Width W/dual Turf Master Tires	72 inches (183 cm)
Width w/single bar tires	47 inches (119 cm)
Width w/dual bar tire	68 inches (173 cm)
Height (top of Roll Bar)	67 inches (170 cm)
Turning Radius	43 inches (109 cm)
Weight	1290 lbs (585 kg)
Fuel Capacity	6.0 gal. (22.7L)
Travel Speed [1]	Infinitely Variable
Low Range (Forward/Reverse)	5.2 mph (8.4 kph)
High Range (Forward/Reverse)	10 mph (16.1 kph)
Shipping Weight w/Crate	1490 lbs (822 kgs)
Shipping Dimensions	79 x 50.5 x 51 inches (201 x 128 x 130 cm)
Standard Features	
Roll Bar	R.O.P.S. Certified
Steering	Power
PTO	Electric Clutch
Easy Shift	Standard

[1]Maximum Speeds may vary with tire size, pressure, and engine RPM

All specifications subject to change without notice or obligation

328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com