

Genie® Z®-62/40 & Z-62/40 TraX™

Specifications

Models	Z-62/40 & Z-62/40 TraX	
Measurements	**US**	**Metric**
Working height max.(1)	67 ft 11 in	20.87 m
Platform height max.	61 ft 11 in	18.87 m
Horizontal reach max.	40 ft 9 in	12.42 m
Up and over clearance max.	25 ft 7 in	7.8 m
A Platform length	3 ft/2 ft 6 in	0.91 m/0.76 m
B Platform width	8 ft/6 ft	2.44 m/1.83 m
C Height - stowed (tires)	8 ft 4 in	2.54 m
C Height - stowed (TraX)	8 ft 6 in	2.59 m
C Height - storage/transport (jib tucked under) (tires)	9 ft 6 in	2.90 m
C Height strorage/transport height (jib tucked under) (TraX)	9 ft 8 in	2.95 m
D Length - stowed (tires)	30 ft 3 in	9.25 m
E Width	8 ft 2 in	2.49 m
F Wheelbase	8 ft 2 in	2.49 m
G Ground clearance - center (tires)	1 ft 3 in	0.41 m
G Ground clearance - center (TraX)	1 ft 5 in	0.43 m
Productivity		
Lift capacity max. - unrestricted	500 lb	227 kg
Platform rotation	180°	
Jib length	5 ft	1.52 m
Vertical jib rotation	135°	
Turntable rotation	360°	
Turntable tailswing	zero	
Drive speed - stowed (tires)(2)	3.0 mph	4.8 km/h
Drive speed - raised (tires)	0.68 mph	1.1 km/h
Gradeability - stowed(2)	30%	
Tilt sensor activation (front to back/side to side)	4.5°/4.5°	
Turning radius - inside/outside (tires, 4WD)	9 ft 2 in/18 ft 9 in	2.80 m/5.71 m
Tires (solid, non-marking)	355/55 D625	
Power		
Power	Diesel	
Auxiliary power unit	12V DC	
Hydraulic tank capacity	35 gal	132 L
Fuel tank capacity	35 gal	132 L
Weight(3) and Floor Loading(4)		
Weight, 2 WS	22,185 lb	10,063 kg
Weight, 4 WS	22,690 lb	10,292 kg
Tire contact pressure	11 psi	75.8 kPa
Occupied floor pressure (tires)	247 psf	11.83 kPa
Sound and Vibration Levels		
Sound Pressure level (ground workstation)	84 dBA	
Sound Pressure level (platform workstation)	75 dBA	
Vibrations	8 ft 2 in/s²	2.5 m/s²

Range of motion Z-62/40/Z-62/40 TraX





(1) The metric equivalent of working height adds 2 m to platform height. The imperial equivalent adds 6 ft to platform height.
(2) Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.
(3) Weight refers to standard configuration and may vary depending on options and/or country standards.
(4) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.

Genie® Z®-62/40 & Z-62/40 TraX™

SKU: Standard Model

- Z-62/40, 2WD*
- **Z6200001AF0003:** Z-62/40, 4WD
- **Z6200001AI0034:** Z-62/40 TraX, 74 hp, Deutz Turbo Diesel
- **Z6200001AF0004:** Z-62/40, 12kW Welder Ready, 4WD

* Build to Order

	Option availability	S	S+	Bt0
Power	49 hp, 36.5 kW, Deutz D2.9L, Diesel, T4f	✔	✔	✔
	49 hp, 36 kW, Perkins 404F-E22T, Turbo Diesel, T4f			❍
	60 hp, 45 kW, Deutz TD2.2L, Turbo Diesel, Stage V (TraX)	✔	✔	✔
	60 hp, 44.7 kW, Ford MSG425 gas/LPG Dual Fuel			❍
	74 hp, 55 kW, Deutz TD2.9L4 turbo diesel, Tier 4f			❍
	Cold weather package			❍
	Diesel air intake pre-cleaner			❍
	Engine gauge package			❍
	LPG tank 33.5 lb		❍	❍
	LPS fire protection rating			❍
	Positive air shutdown system			❍
	Auto engine fault shutdown	✔	✔	✔
Platform	6ft/1.83m dual-entry platform with side swing gate			❍
	8ft/2.44m tri-entry platform with side swing gate	✔	✔	✔
	8ft/2.44m tri-entry platform with side swing gate	✔	✔	✔
	Dual axis joystick steering	✔	✔	✔
	Thumb rocker steering			❍
	Air line to platform			❍
	Aircraft protection kit			❍
	Control box covers		❍	❍
	Lift Guard Full Mesh panels			❍
	Lift Guard Half Mesh panels			❍
	Light Package: drive and work lights		❍	❍
	Platform auxiliary top rail			❍
	3kW AC Generator, 110V/60Hz			❍
	3kW AC Generator, 220V/50Hz			❍
	12kW Welder ready			❍
	5ft/1.52m Jib	✔	✔	✔
	AC Power cord to platform	✔	✔	✔
	Drive enable system	✔	✔	✔
	Horn	✔	✔	✔
	Lift Guard Contact Alarm	✔	✔	✔
	Lift Tools Work Tray	✔	✔	✔
	Platform load sense system	✔	✔	✔
	Proportional controls	✔	✔	✔
	Self-leveling platform	✔	✔	✔
	Travel alarm package: flashing beacons, descent, travel and tilt alarms	✔	✔	✔
Chassis	Lift Connect Telematics	✔	✔	✔
	Lift Connect with Access Manager upgrade		❍	❍
	Biodegradable hydraulic oil			❍
	Cold weather hydraulic oil			❍
	Fire resistant hydraulic oil			❍
	Rough terrain, foam-filled tires	✔	✔	✔
	Rough terrain, foam-filled, non-marking tires		❍	❍
	TraX quadra track drive system			❍
	2 wheel steering	✔	✔	✔
	4 wheel steering			❍
	Deluxe hostile environment kit			❍
	Hostile environment kit			❍
	Tow package			❍
	2 speed wheel motors	✔	✔	✔
	Active oscillating axle	✔	✔	✔
	Chassis tilt drive function cut-out	✔	✔	✔
	Dual parallelogram lift linkage	✔	✔	✔
	Hour meter	✔	✔	✔
	Hydraulic oil cooler	✔	✔	✔

Positive air shutdown Deutz engines only

- S Standard
- S+ Standard +
- Bt0 Build to Order
- ✔ Standard Features
- ❍ Options



Zero Tailswing



Rugged Terrainability



Genie FastMast



Genie Genuine Accessories(1)

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

04/22

© 2022 Terex Corporation