Specifications

NOTE: Weights are with typical optional equipment. Weights with other optional equipment vary.

The maximum static vertical load for this implement is achieved with the implement folded in road transport position and equipped with authorized attachments.

Item	Measurement	Specification
Maximum Static Vertical Load on Tractor Drawbar	Weight (40 ft Tool)	1796 kg (3960 lb)

Item	Measurement	Specification
Maximum Static Vertical Load on Tractor Drawbar	Weight (56 ft TBT Tool)	2349 kg (5180 lb)

Type	Drawn 3 or 5-Section, Fixed Frame With Over-Center Fold			
Hydraulics:				
Working Pressure	20 680 kPa (206.8 bar) (3000 psi)			
Burst Pressure	29 303 kPa (293 bar) (4250 psi)			
Opener Depth Control	Accumulator Pressure			
Fertilizer Shank:				
Hydraulic Cushion Breakout Force	Adjustable from 889-2224 N (200-500 lbf)			
Tip Wear Surface	Carbide			
Seed Shank:				
Spring Breakout Force	44-534 N (10-120 lbf)			
Vertical Adjustment	6 mm (1/4 in) Increments			
Horizontal Adjustment	9 mm (3/8 in) Increments			
Press Wheel:				
Type	Rotational Molded or Semi-Pneumatic			
Down Force	Adjustable from 444 to 979 N (100 to 220 lbf)			
Tire Pressure:				
Center and Wing Frame	413 kPa (4.13 bar) (60 psi)			
Caster Wheel	248 kPa (2.48 bar) (36 psi)			
Row Spacing:				
Seed Openers	23 cm (9 in) and 8 cm (3 in) Paired Row Seed Tube			
Seed Openers	30 cm (12 in) Side Band Seed Tube			
Fertilizer Openers	30 cm (12 in) Shank and Fertilizer Tube			
Width, Height, and Weight:				
Machine	**Working Width**	**Transport Width**	**Transport Height**	**Weight**
3-Section	12.2 m (40 ft)	5.7 m (19 ft)	5.4 m (17.6 ft)	9535 kg (21 020 lb)
5-Section	17.1 m (56 ft)	5.7 m (19 ft)	4.8 m (15.8 ft)	13 600 kg (30 000 lb)
Specifications subject to change without notice.				

Copyright © 2013 Deere & Company.
All Rights Reserved.