Specifications

Cutterbar	
Type	Straight Line Knife Drive System, Single or Dual Knife
Length	7.7 m (25.2 ft.), 9.2 m (30.2 ft.), 10.7 m (35 ft.), 12.2 m (40 ft.)
Knife Speed	520 cycles per minute
Pickup Reel	
Number of slats	6 (625D has optional 8 bat reel)
Fingers	Nylon (625D has optional steel tine fingers)
Diameter	1,067 mm (42 in.)
Height Control	Hydraulic
Speed Control	Hydraulic
Operating Speeds	6—70 rpm (6—54 rpm optional)
Draper Belts	
Width	Side Belts: 1010 mm (40 in.)
	Center Belt: 1393 mm (55 in.)
Operating Speed	Side Belts: 0—223 m/min. (0—735 ft./min.).
	Center Belt: 0—212 m/min. (0—695 ft./min.)
Speed Control	Hydraulic
Feed Drum	
Diameter	406 mm (16 in.)
Feed Drum Fingers	Heavy-duty, round 16 mm (5/8 in.) diameter with breakaway notch and retainer.
Number of Fingers	18
Auger Finger Pattern	Dual Chevron, retracting
Finger Reach	152 mm (6 in.)
Operating Speed	195 rpm
Platform Length	
625D	8.49 m (27.9 ft.)
630D	10 m (32.9 ft.)
635D	11.6 m (37.9 ft.)
640D	13.1 m (42.9 ft.)

KR43067,000040C-19-20090707

Copyright © 2013 Deere & Company.
All Rights Reserved.