Current Country

United States Change

Language

English - EN

Compare

Print

BP15

Belt Pickup Platform

Find a Dealer

View Product Brochure

Find Parts

Warranty and Protection Plans

The BP15 Belt Pickup delivers superior efficiency and reli productivity with its advanced design and seamless compatibility with exceptional performance in diverse field

Current Country

United States Change

Language

English - EN

3 ft Opening (915 mm) **neter**

57 mm Float Range **Bel** **5 m/min)**

Benefits

Helping You Harvest with Confidence

Changing harvest conditions can be overwhelming. John Deere automation takes the pressure off by optimizing combine settings, guiding precise turns, and managing unloads on the go—protecting yield, reducing grain loss, delivering clean samples, and keeping you focused on feeding the machine, and less on adjusting, steering, or unloading.

Make Every Minute of the Harvest Window Count

John Deere delivers harvesting solutions matched to your operation, with a full portfolio of combines and front end equipment to hit your harvest window. Automation like Machine Sync, Auto Unload, and Predictive Ground Speed boost productivity, while integrated technology, parts, and Precision Upgrades help your combine adapt to changing crops and conditions—season after season.

Analyze Key Insi Decisions Next

Harvest data becom advantage. Yield ma machine analytics i Operations Center placement, fertility selections. Combine upgrades and auto into consistent exec stage for better res

1 / 2

Specifications

Add to Compare

Collapse All

Total Picking Width	14.9 ft
Cutting Width	14.9 ft
Number Of Fingers Per Belt	84
Auger Diameter	26.0 in.
Auger Fingers	Steel with breakaway notch; Diameter: 0.625 in. (15.9 mm)

Current Country
United States Change
Language
English - EN

Header

Transport Widths	17.5 in.

Pickup Belts

Width Of Belts	3.7 ft
Number Of Belts Per Pickup	4
Total Picking Width	14.9 ft
Number Of Rollers	2
Cutting Width	14.9 ft

Pickup Fingers

Type	Plastic
Number Of Fingers Per Belt	84

Auger

Float Range	2.25 in.
Auger Diameter	26.0 in.
Auger Fingers	Steel with breakaway notch; Diameter: 0.625 in. (15.9 mm)
Number Of Auger Fingers	19 STS, maximum 22
Auger Finger Pattern	In-line, retracting
Finger Reach	6.0 in.
Operating Speed	216.0 rpm

Current Country
United States Change
Language
English - EN

Tires

Adjustment	Toolless
Pressure	103.4 kPa
Pressure	15.0 psi

Crop Deflector

Crop Deflector	Factory installed

Weight

Approximate Shipping Weight (Includes Shipping Skids)	3630.0 lb.

Date Collected
2020-06-15

Current Country
United States Change

Language
English - EN

See Less

Download Spec Sheet

Images of equipment models may be digitally or AI generated, are for illustratio nge. Equipment models shown are typically base models and may not reflect all features, options, or attachments. Equipment availability may be limited. See your John Deere dealer for additional information. Features and specifications are based on published information at the time of publication and are subject to change without notice. See your dealer for available models, options, attachments, and pricing. Product options and accessories may not be available in all regions. Equipment, models, features, options, attachments, and prices may vary by dealer. John Deere reserves the right to change specifications, model features, design, and price of the products described here without notice.

Subscribe for more

Receive e-mail news & offers from John Deere

Subscribe Now

Have any thoughts?

Take Survey

Products & Support

Buy Parts
Find a Dealer

Company Information

Careers
Ethics & Compliance
Governance

News & Publications

Newsroom
Content Library
The Furrow
The Dirt
The Landing
Power Connect

Connect with John Deere

Visit Us
Buy Merchandise
John Deere Kids
John Deere Rewards

United States

Privacy & Data | Accessibility | Terms of Use | Cookie Statement | Contact Us | Cookie Preferences

Copyright © 2026 Deere & Company. All Rights Reserved.