Specifications

Cutterbar	
Type	4-in. Knife system with in-line gearbox
Cutterbar Angle	10 degrees
Cutterbar Length	5.5 m, 6.1 m, 6.7 m, 7.6 m, 9.2 m, 10.7 m (18 ft, 20 ft, 22 ft, 25 ft, and 30 ft, 35 ft)
Flex Cutterbar Float Range	152.4 mm (6.0 in.)
Tilt Adjustment	17 degrees (located on feeder house)
Knife Sections	Heavy-duty, over-serrated
Guards	Forged steel, heat-treated
Knife Speed	512 cycles/min
Backshaft	
Operating speed	520 rpm
Platform Auger	
Diameter	660 mm (26 in.)
Operating Speed	152 rpm 135 rpm (slow down) 170 rpm (speedup)
Reel	
Number of Slats	6
Diameter	1,067 mm (42 in.)
Height Control	Hydraulic
Speed Control	Hydraulic
Operating Speeds	6-70 rpm
Hydraulics	
Reel Motor Displacement (Per Revolution)	0.196L (11.9 cu in.)
Reel Drive System Pressure	14000 ± 1000 kPa (2000 ± 150 psi)
Reel Fore/Aft Stroke	359 mm (14.1 in.)

SS43267,0000249-19-20130516

Copyright © 2013 Deere & Company.
All Rights Reserved.