KOMATSU

WA200-8

Tier 4 Final Engine

WHEEL LOADER

WA200



Photos may include optional equipment.

NET HORSEPOWER
126 HP @ 2000 rpm
94 kW @ 2000 rpm

OPERATING WEIGHT
25,827– 26,489 lb
11715 – 12015 kg

BUCKET CAPACITY
2.6 – 3.1 yd³
2.0 – 2.4 m³

WALK-AROUND



Photos may include optional equipment.

NET HORSEPOWER	OPERATING WEIGHT	BUCKET CAPACITY
126 HP @ 2000 rpm	**25,827– 26,489 lb**	**2.6 – 3.1 yd³**
94 kW @ 2000 rpm	11715 – 12015 kg	2.0 – 2.4 m³

KOMATSU CARE®

AGILITY AND PRODUCTIVITY

Proven, Fourth Generation Hydrostatic Transmission:
- Quick Acceleration
- Dynamic Braking
- Variable Traction Control System
- Creeping Mode

Versatile Parallel Z-bar (PZ) linkage:
- Parallel lift for handling pallets or pipe
- Large breakout force for earth work



A powerful Komatsu SAA4D107E-3 engine provides a net output of 94 kW **126 HP** with up to four percent improved fuel consumption. This engine is EPA Tier 4 Final emissions certified.

New Variable Geometry Turbocharger (VGT) provides optimum air flow under all speed and load conditions. This Tier 4 Final version has improved performance.

Komatsu Diesel Oxidation Catalyst (KDOC) and new Selective Catalytic Reduction (SCR) systems reduce hydrocarbons, carbon monoxide, and NOx without interfering with daily operation.

Increased cooling capacity
- Auto-reversing fan is standard
- Wider core coolers
- Cooling system volume increased by 7.5%

Fluid neutral or better
Combined fuel and DEF consumption is equal to or less than the WA200-7 fuel consumption.

New spacious cab provides the operator with improved comfort and visibility.

Multi-function mono lever with proportional control switch.

New high resolution monitor panel:
- Enhanced and intuitive on-board diagnostics
- Integrated with KOMTRAX® Level 5
- Integrated with Komatsu Tier 4 Final technology

New rearview monitoring system is standard.

New high capacity air suspension seat with heat is standard.

Battery disconnect switch allows a technician to disconnect the power supply before servicing the machine.

Energy saving guidance:
- Six operator guiding messages
- Enhanced ecology gauge

New Komatsu auto idle shutdown helps reduce idle time and operating costs.

The **KOMTRAX®** telematics system is standard on Komatsu equipment with no subscription fees throughout the life of the machine. Using wireless technology, **KOMTRAX®** transmits valuable information such as location, utilization, and maintenance records to a PC or smart-phone app. Custom machine reports are provided for identifying machine efficiency and operating trends. **KOMTRAX®** also provides advanced machine troubleshooting capabilities by continuously monitoring machine health.

New operator identification system tracks machine operation for up to100 operators.


Swing-out cooler design allows access to service and clean the cooler assembly.

PRODUCTIVITY & ECOLOGY FEATURES

KOMATSU NEW ENGINE TECHNOLOGIES

New Tier 4 Final Engine


The Komatsu SAA4D107E-3 engine is EPA Tier 4 Final emissions certified, reduces fuel consumption, and provides exceptional performance. Based on Komatsu proprietary technologies developed over many years, this new diesel engine reduces nitrogen oxides (NOx) compared to Tier 4 interim levels.



Technologies Applied to New Engine


Heavy-Duty After Treatment System

This new system combines Komatsu Diesel Oxidation Catalyst (KDOC) and Selective Catalytic Reduction (SCR). The SCR NOx reduction system injects the Diesel Exhaust Fluid (DEF) at the proper rate, thereby decomposing NOx into non-toxic water (H_2O) and nitrogen gas (N_2).



Variable Geometry Turbocharger (VGT) system

The VGT provides optimal air flow under all engine speed and load conditions. The upgraded version provides better exhaust temperature management.



Heavy-Duty Cooled Exhaust Gas Recirculation (EGR) System

The system recirculates a portion of exhaust gas into the air intake and lowers combustion temperatures, thereby reducing NOx emissions. EGR gas flow is lower for Tier 4 Final with the addition of SCR technology. The system drastically reduces NOx while reducing fuel consumption.

Advanced Electronic Control System

An improved electronic control system more effectively manages engine parameters such as airflow rate, fuel injection parameters, and after treatment function. The control system also provides enhanced diagnostics through the monitor panel. Additionally, managing information via KOMTRAX helps customers track required maintenance.

Heavy-Duty High-Pressure Common Rail (HPCR) fuel injection system


The system is specifically designed to achieve the optimal injection of fuel for near- complete combustion, which helps reduce Particulate Matter (PM) emissions.

Hydrostatic Transmission (HST)

The HST provides quick travel response and aggressive drive into the pile. Full auto-shifting eliminates any gear shifting and kick-down operation to allow the operator to concentrate on digging and loading. The HST also acts as a dynamic brake to slow the loader. This dramatically extends the life of the wet disc brakes.


1-Pump, 2 Motor System

The 1-pump, 2 motor system allows for high-efficiency and high tractive effort. Engine power is transmitted hydraulically to a transfer case, then mechanically out to the differentials and the four driving wheels.



Variable Traction Control System


The variable speed control system is designed to adjust the tractive effort for each working condition. S-mode reduces tire spin in slippery or snowy conditions. Tractive effort can be adjusted in three stages when traction control switch is ON. Max traction provides the full, 100%, tractive effort.



Creep Mode


Creep mode limits the travel speed in 1st speed range, while still allowing for full hydraulic flow.





Komatsu Auto Idle Shutdown

In order to reduce unwanted idle time, Komatsu offers Komatsu auto idle shutdown. This function will shut the engine off and apply the parking brake and hydraulic lock after a preset idle time limit. This time limit can be set by the operator or service technician and may range from three to 60 minutes. It can also be deactivated by the operator.



OPERATOR ENVIRONMENT



New Operator Seat

A new standard, heated, air-suspension seat provides enhanced support on rough roads and dampens machine vibrations, providing a more comfortable ride for the operator. The angle of the armrest is fully adjustable for optimum operator comfort. A secondary F-N-R switch is incorporated into the standard multi-function mono lever.




Tiltable / Telescopic Steering Wheel

The operator can tilt and telescope the steering wheel to allow maximum comfort and control. The two-spoke steering wheel allows maximum visibility of the monitor panel and the forward work environment.



Low Noise Design

Operator's ear noise level: 68 dB(A)*
Dynamic noise level (outside): 104 dB(A)**



The large ROPS/FOPS cab is mounted with Komatsu's unique viscous mounts. The low-noise engine, hydraulically-driven fan, and hydraulic pumps are mounted with rubber cushions, and the cab sealing is improved to provide a quiet, low-vibration, comfortable operating environment.

* *ISO 6396: 2008*
** *ISO 6395: 2008*

Increased Cab Storage Area

The WA200-8 cab features a heated/cooled storage compartment on the right side of the cab to allow the operator to store items such as a beverage or lunch.





Standard Rearview Monitoring System


The dedicated, full-color monitor on the right side of the cab provides the operator with a rearview from the machine. This monitor can be always on or only on when the loader shifts into reverse. Guidelines provide the operator with visual cues for the width of the loader.






Auxiliary Input (MP3 Jack) 12 V Outlets

An Aux input for audio devices is standard, as well as two 12 volt outlets. These are all located on the rear wall of the cab.



Secondary Engine Shutdown Switch

The engine stop switch enables machine shutdown when accessing the key switch is not possible.



WORKING ENVIRONMENT



Easy Entry and Exit

The WA200-8 has an inclined ladder with wide steps and well-placed hand holds to ease entry and exit from the cab. The door latch can be reached from ground level to ease machine access.

Electronically Controlled Suspension System

The standard Electronically Controlled Suspension System or ride control system uses an accumulator, which absorbs some of the shock in the boom arm, giving the operator a much smoother ride. This reduces operator fatigue and reduces material spillage during load and carry operations. Ride control is speed sensitive and the activation speed can be adjusted in the monitor panel.

Multi-Function Mono Lever

The multi-function mono lever with EPC control for 3rd spool is standard. It includes a forward-neutral-reverse switch for quick and easy travel. Third spool attachments can be set to continual or proportional control via the monitor panel. This allows the operator to control the boom, bucket and attachment, all with a single lever.



Attachment Selector Switch

Coupler equipped machines, which use buckets and forks, require a different flat level setting when switching between attachments. The attachment selector switch found in coupler equipped machines tells the loader which flat level to use.



INFORMATION & COMMUNICATION TECHNOLOGY

New High Resolution LCD Monitor Panel

The new seven inch color LCD monitor panel displays operational information, ecology guidance and maintenance records. Information such as traction mode, coolant temp, oil and fuel levels are easy to read and help keep the operator informed of the machine's settings and conditions.

Machine monitor


1. LCD unit
2. LED unit
3. Engine tachometer
4. Speedometer
5. Ecology gauge
6. Air conditioner display
7. Traction level
8. Engine coolant temperature gauge
9. Fuel gauge
10. HST oil temperature gauge
11. Variable speed display
12. Message pilot lamp
13. Pilot lamps
14. DEF level gauge


Switch panel

1. Air conditioner switches / Numeral key pad
2. Function switches

Visual user menu

Pressing the menu button on the switch panel accesses the user-menu screen. The menus are grouped by function, with easy-to-understand, intuitive icons for easier machine operation.






1. Energy saving guidance
2. Machine settings
3. Aftertreatment devices regeneration
4. SCR information
5. Maintenance
6. Monitor setting
7. Mail check



Operator Identification function

An operator identification (ID) code can be set for each operator, and used to manage operation information of individual machines through KOMTRAX. Data sent from KOMTRAX can be used to analyze operation status by operator job, as well as by machine.



Monitor Panel with troubleshooting function minimizes downtime

Various meters, gauges and warning functions are centrally arranged on the monitor panel. The monitor simplifies start-up inspection and warns the operator with a lamp and buzzer if any abnormalities occur. Warnings are indicated in four levels, which the operator must acknowledge and clear. Replacement times for oil and filters are also indicated.




MAINTENANCE FEATURES



Engine Compartment

The WA200-8 engine compartment is designed for easy serviceability. Placement of maintenance items, such as filters, dipsticks, and oil-fill locations are laid out for easy-to-reach access.



Cab Air Filter

The inside and outside air filters can be replaced easily without the need for tools. The outside filter is located behind a lockable door for security.


Inside air filter



Outside air filter

Maintenance Information

"Maintenance time caution lamp" display

When the time before required maintenance is less than 30 hours*, the maintenance-time monitor appears. Pressing the menu switch displays the maintenance screen.

* : The setting can be changed within the range between 10 and 200 hours.



Maintenance screen

Supports DEF level and refill timing

The DEF level gauge is displayed continuously on the monitor panel. In addition, when the refill timing is reached, the DEF-low-level icon appears to alert the operator.



DEF level gauge



DEF low level guidance

Side-opening Gull-wing Engine Doors

The large, gull-wing-type engine doors require minimal effort to open and close, thanks to gas assisted struts. The doors make access and daily maintenance easy. Large steps on the side of the frame also enhance accessibility.



Automatic Reversing Fan

The engine cooling fan is hydraulically driven. It can be set to reverse automatically during operation. Fan reverse mode and timing can be controlled through the monitor.



Swing-Out Type Cooling Fan and Wide Core Radiator

The cooling fan swings out for cleaning. The coolers feature wider fin spacing cooling to reduce clogging.



Battery Disconnect Switch

The battery disconnect switch is located on the right side of the machine. This can be used to disconnect power when performing service work on the machine.



DEF Tank

The DEF tank is ground-level accessible on the left side of the machine near the cab door for easy access. The tank features a sight glass that helps prevent overfilling.



Full Rear Fenders (Option)

The WA200-8 has a new rear fender option. The rear fenders open upward and use gas-assist struts, which require low lift force.

The fenders swing up with the gull-wing doors to give the technician easy access to the engine compartment. Mud flaps are also included on the rear fenders.



KOMATSU PARTS & SERVICE SUPPORT

KOMATSU CARE

Program Includes:
The WA200-8 comes standard with complimentary factory scheduled maintenance for the first 3 Years or 2,000 Hours, whichever comes first.*

Planned Maintenance Intervals at:
500/1000/1500/2000 hour intervals. (250 hr. initial interval for some products) Complimentary Maintenance Interval includes: Replacement of Oils & Fluid Filters with genuine Komatsu Parts, 50-Point inspection, Komatsu Oil & Wear Analysis Sampling (KOWA) / Travel & Mileage (distance set by distributor; additional charges may apply)

Benefits of Using Komatsu CARE

- Assurance of Proper Maintenance with OEM Parts & Service
- Increased Uptime & Efficiency
- Factory Certified Technicians Performing Work
- Cost of Ownership Savings
- Transferable Upon Resale

Interval PM	i250	500	1000	1500	2000
CLEAN AC FRESH AND RECIRC AIR FILTERS	✓				
REPLACE HYDRAULIC OIL FILTER ELEMENT	✓				✓
REPLACE HST OIL FILTER	✓		✓		✓
KOWA SAMPLING – (Engine, Front Axle & Rear Axle, Hydraulics, Transfer case)	✓	✓	✓	✓	✓
CHECK AND CLEAN AIR CLEANER	✓	✓	✓	✓	✓
CHECK AND CLEAN FUEL BREATHER ELEMENT	✓	✓	✓	✓	✓
LUBRICATE REAR AXLE PIVOT PIN	✓	✓	✓	✓	✓
LUBRICATE WORK EQUIPMENT	✓	✓	✓	✓	✓
DRAIN SEDIMENT FROM FUEL TANK	✓	✓	✓	✓	✓
COMPLETE 50 POINT INSPECTION FORM; LEAVE PINK COPY WITH CUSTOMER OR IN CAB	✓	✓	✓	✓	✓
RESET MONITOR PANEL MAINTENANCE COUNTER FOR APPROPRIATE ITEMS	✓	✓	✓	✓	✓
CHANGE ENGINE OIL		✓	✓	✓	✓
REPLACE ENGINE OIL FILTER		✓	✓	✓	✓
REPLACE AC FRESH & RECIRC AIR FILTERS		✓	✓	✓	✓
REPLACE FUEL PRE-FILTER		✓	✓	✓	✓
REPLACE FUEL MAIN FILTER			✓		✓
CHANGE OIL IN TRANSFER CASE			✓		✓
CLEAN TRANSFER CASE STRAINER			✓		✓
CLEAN TRANSFER BREATHER			✓		✓
LUBRICATE CENTER HINGE PIN			✓		✓
CHANGE OIL IN HYDRAULIC TANK					✓
REPLACE HYDRAULIC TANK BREATHER ELEMENT					✓
CLEAN HYDRAULIC TANK STRAINER					✓
CHANGE FRONT AND REAR AXLE OIL					✓
CLEAN BRAKE CIRCUIT STRAINER					✓
REPLACE KCCV FILTER					✓
REPLACE HST DRAIN OIL FILTER					✓
REPLACE DEF PUMP FILTER					✓
REPLACE DEF TANK BREATHER					✓
FACTORY TRAINED TECHNICIAN LABOR	✓	✓	✓	✓	✓

* Certain exclusions and limitations apply. Refer to the customer certificate for complete program details and eligibility. Komatsu® and Komatsu Care® are registered trademarks of Komatsu Ltd. Copyright 2017 Komatsu America Corp.

Komatsu CARE® – Extended Coverage

- Extended Coverage can provide peace of mind by protecting customers from unplanned expenses that effect cash flow
- Purchasing extended coverage locks-in the cost of covered parts and labor for the coverage period and helps turn these into fixed costs



Komatsu Parts Support

- 24/7/365 to fulfill your parts needs
- 9 parts Distribution Centers strategically located across the U.S. and Canada
- Distributor network of more than 300 locations across U.S. and Canada to serve you
- Online part ordering through Komatsu eParts
- Remanufactured components with same-as-new warranties at a significant cost reduction



Komatsu Oil and Wear Analysis (KOWA)

- KOWA detects fuel dilution, coolant leaks, and measures wear metals
- Proactively maintain your equipment
- Maximize availability and performance
- Can identify potential problems before they lead to major repairs
- Reduce life cycle cost by extending component life

KOMTRAX EQUIPMENT MONITORING

GET THE WHOLE STORY WITH KOMTRAX®

✓ WHAT

- KOMTRAX is Komatsu's remote equipment monitoring and management system
- KOMTRAX **continuously monitors and records** machine health and operational data
- Information such as fuel consumption, utilization, and a detailed history **lowering owning and operating cost**

✓ WHO

- KOMTRAX is **standard** equipment on all Komatsu construction products

✓ WHEN

- Know when your machines are **running or idling** and make decisions that will improve your fleet utilization
- Detailed movement records ensure you know when and where your equipment is moved
- Up to date records allow you to **know when maintenance is due** and help you plan for future maintenance needs



✓ WHERE

- KOMTRAX data **can be accessed virtually anywhere** through your computer, the web or your smart phone
- Automatic alerts keep fleet managers up to date on the latest machine notifications

✓ WHY

- Knowledge is power - **make informed decisions** to manage your fleet better
- Knowing your idle time and fuel consumption will help maximize your machine efficiency
- **Take control of your equipment** - any time, anywhere



KOMTRAX®
For construction and compact equipment.

KOMTRAX Plus®
For production and mining class machines.

SPECIFICATIONS

ENGINE

Model ..... Komatsu SAA4D107E-3*
Type ..... Water-cooled, 4-cycle
Aspiration ..... Variable geometry, turbo-charged, after-cooled, cooled EGR
Number of cylinders 4
Bore ..... 107 mm **4.21"**
Stroke ..... 124 mm **4.88"**
Piston displacement ..... 4.46 ltr **272 in³**
Governor ..... All-speed, electronic
Horsepower:
SAE J1995 ..... Gross 95.2 kW **128 HP**
ISO 9249 / SAE J1349 ..... Net 94 kW **126 HP**
Rated rpm ..... 2000 rpm
Fan drive method for radiator cooling ..... Hydraulic
Fuel system ..... Direct injection
Lubrication system:
Method ..... Gear pump, force-lubrication
Filter ..... Full-flow type
Air cleaner ..... Dry type with double elements and dust evacuator, plus dust indicator

*EPA Tier 4 Final emissions certified

TRANSMISSION

Transmission ..... Hydrostatic, 1 pump, 2 motors with speed range select

Travel speed	Forward	Reverse
1st	0 - 14.3 km/h **0 - 8.9 mph**	0 - 14.3 km/h **0 - 8.9 mph**
2nd	14.3 km/h **8.9 mph**	14.3 km/h **8.9 mph**
3rd	23.2 km/h **14.4 mph**	23.2 km/h **14.4 mph**
4th	38.0 km/h **23.6 mph**	38.0 km/h **23.6 mph**

Measured with 20.5-R25 tires

AXLES AND FINAL DRIVES

Drive system ..... Four-wheel drive
Front ..... Fixed, semi-floating
Rear ..... Center-pin support, semi-floating, 24° total oscillation
Reduction gear ..... Spiral bevel gear
Differential gear ..... Torque proportioning
Final reduction gear ..... Planetary gear, single reduction

BRAKES

Service brakes ..... Hydraulically actuated, wet disc brakes actuate on four wheels
Parking brake ..... Wet, multi-disc brake on transfer output shaft
Secondary brake ..... One of dual service brake circuits is commonly used

STEERING SYSTEM

Type ..... Articulated type, fully-hydraulic power steering
Steering angle ..... 38° each direction (40° to max end stop)
Minimum turning radius at the center of outside tire ..... 4880 mm **16' 0"**

HYDRAULIC SYSTEM


Steering system:
Hydraulic pump ..... Gear type pump
Capacity ..... 85 ltr/min **22.5 U.S. gal/min** at rated rpm
Relief valve setting ..... 20.6 MPa 210 kgf/cm² **3,000 psi**
Hydraulic cylinders:
Type ..... Double-acting, piston type
Number of cylinders 2
Bore x stroke ..... 70 mm x 453 mm **2.76" x 17.8"**
Loader control:
Hydraulic pump ..... Gear type pump
Capacity ..... 54 ltr/min **14.3 U.S gal/min** at rated rpm
Relief valve setting ..... 20.6 MPa 210 kgf/cm² **3,000 psi**
Hydraulic cylinders:
Type ..... Double-acting, piston type
Number of cylinders—bore x stroke:
Lift cylinder ..... 2- 125 mm x 673.5 mm **4.9" x 26.5"**
Bucket cylinder ..... 1- 150 mm x 504 mm **5.9" x 19.8"**
Control valve ..... 2-spool type
Control positions:
Boom ..... Raise, hold, lower, and float
Bucket ..... Tilt-back, hold, and dump
Hydraulic cycle time (rated load in bucket)
Raise ..... 5.7 sec
Dump ..... 1.9 sec
Lower (Empty) ..... 3.2 sec

SERVICE REFILL CAPACITIES

Cooling system	26.5 ltr	**7.0 U.S. gal**
Fuel tank	177 ltr	**46.8 U.S. gal**
Engine	15.5 ltr	**4.1 U.S. gal**
Hydraulic system	58 ltr	**15.3 U.S. gal**
Axle front	18.5 ltr	**4.9 U.S. gal**
Axle rear	18 ltr	**4.8 U.S. gal**
Transfer case	5 ltr	**1.3 U.S. gal**
DEF tank	14 ltr	**3.7 U.S. gal**

BUCKET SELECTION GUIDE

Pin-on Buckets




Light Material Bucket with BOCE (Scooping and loading of light material)

General Purpose Bucket with BOCE (Loading and excavating of soil, sand and a variety of other commonly handled material)

Excavating Bucket with BOCE (Loading and excavating of soil, sand and a variety of other commonly handled material)


Quick Coupler Buckets




General Purpose Bucket with BOCE (Loading and excavating of soil, sand and a variety of other commonly handled material)

DIMENSIONS

Measured with 20.5-R25(L3) Tires, ROPS/FOPS cab





	Tread	1930 mm	**6'4"**
	Width over tires	2470 mm	**8'1"**
A	Wheelbase	2840 mm	**9'4"**
B	Hinge pin height, max. height	3885 mm	**12'9"**
C	Hinge pin height, carry position	425 mm	**1'5"**
D	Ground clearance	495 mm	**1'7"**
E	Hitch height	965 mm	**3'2"**
F	Overall height, top of the stack	3010 mm	**9'10"**
G	Overall height, ROPS cab	3200 mm	**10'6"**

BUCKET

		General Purpose Bucket w/ Pin On B.O.C.E.	Light Material Bucket w/ Pin On B.O.C.E.	General Purpose Bucket w/ Quick Coupler B.O.C.E.
	Bucket capacity: heaped	2.0 m³ **2.6 yd³**	2.4 m³ **3.1 yd³**	1.9 m³ **2.5 yd³**
	struck	1.7 m³ **2.2 yd³**	2.0 m³ **2.6 yd³**	1.6 m³ **2.1 yd³**
	Bucket width	2550 mm **8'4"**	2550 mm **8'4"**	2550 mm **8'4"**
	Bucket weight	890 kg **1,926 lb**	965 kg **2,127 lb**	885 kg **1,951 lb**
H	Dumping clearance, max. height and 45° dump angle*	2965 mm **9'8"**	2875 mm **9'5"**	2810 mm **9'3"**
I	Reach at max. height and 45° dump angle*	950 mm **3'1"**	1035 mm **3'5"**	1075 mm **3'6"**
J	Reach at 2130 mm **7'** clearance and 45° dump angle*	1580 mm **5'2"**	1625 mm **5'4"**	1630 mm **5'4"**
K	Reach with arm horizontal and bucket level*	2315 mm **7'7"**	2440 mm **8'0"**	2515 mm **8'3"**
L	Operating height (fully raised)	5095 mm **16'8"**	5215 mm **17'1"**	5220 mm **17'2"**
M	Overall length (bucket on ground)	7130 mm **23'4"**	7255 mm **23'10"**	7350 mm **24'1"**
	Loader clearance circle (bucket at carry, outside corner of bucket)	11860 mm **38'11"**	11930 mm **39'2"**	11965 mm **39'3"**
	Digging depth: 0°	110 mm **4"**	110 mm **4"**	120 mm **5"**
	10°	295 mm **12"**	320 mm **13"**	340 mm **13"**
	Static tipping load: straight	8725 kg **19,235 lb**	8650 kg **19,070 lb**	8525 kg **18,794 lb**
	40° full turn	7645 kg **16,854 lb**	7570 kg **16,689 lb**	7450 kg **16,424 lb**
	Breakout force	108 kN 11000 kgf **24,251 lb**	107 kN 10920 kgf **24,075 lb**	96 kN 9755 kgf **21,506 lb**
	Operating weight	11715 kg **25,827 lb**	11790 kg **25,993 lb**	12015 kg **26,489 lb**

***At the end of tooth or B.O.C.E.**

All dimensions, weights, and performance values based on ISO 7131, ISO 14397-1 and ISO 7546 standards. Static tipping load and operating weight shown include lubricant, coolant, full fuel tank, ROPS cab and operator. Machine stability and operating weight affected by tire size and attachments.

FORK

			Fork With Quick Coupler
O	Fork tine length		1220 mm **4'0"**
P	Ground to top of tine at maximum lift		3740 mm **12'3"**
Q	Reach at maximum lift		810 mm **2'8"**
R	Ground to top of tine - boom and tine level		1750 mm **5'9"**
S	Reach - boom and tine level		1715 mm **5'8"**
T	Reach - tine level on ground		1110 mm **3'8"**
U	Overall length - tine level on ground		7775 mm **25'6"**
	Static tipping load - boom level: fork level, tine center	straight	6095 kg **13,437 lb**
		40° full turn	5340 kg **11,773 lb**
	Operating weight		11705 kg **25,805 lb**

Operating load per SAE J1197 (Oct, 2011), 50% of static tipping load.

Static tipping load and operating weight shown include lubricant, coolant, full fuel tank, ROPS cab and operator. Machine stability and operating weight affected by tire size and attachments.

WEIGHT CHANGES

Tires or attachments	Change in operating weight		Change in tipping load				Width over tires		Ground clearance		Change in vertical dimensions	
			Straight		Full turn							
	kg	lb	kg	lb	kg	lb	mm	ft in	mm	ft in	mm	ft in
17.5-25-12PR (L2)	-610	**-1345**	-405	**-893**	-405	**-893**	2375	**7'10"**	425	**1'5"**	-70	**-3"**
20.5-R25 (L2)	+40	**+88**	+25	**+55**	+25	**+55**	2470	**8'1"**	495	**1'7"**	0	**0**

STANDARD EQUIPMENT

- 2-spool valve for boom and bucket control
- Alternator, 24 V/ 90 A
- Automatic hydraulic-driven fan with automatic reverse rotation
- Back-up alarm
- Batteries, 92 Ah/12V (2), 680 CCA
- Battery disconnect
- Boom kick-out, in-cab adjustable
- Bucket positioner
- Color, rear-view camera and monitor
- Counterweight, standard
- Electronically Controlled Suspension System
- Engine, Komatsu SAA4D107E-3 diesel
- Engine shut-off system, electric
- Equipment Management Monitoring System (EMMS)
  - Lights (central warning, brake oil pressure, engine oil pressure, parking brake, cooling fan reverse, KDPF restriction, seat belt caution, Komtrax message)
  - Gauges (DEF level, engine coolant temperature, ecology, fuel level, HST oil temperature, speedometer/tachometer), variable speed display
- Front fenders
- Fuel pre-filter with water separator
- Horn, electric
- Hydrostatic transmission
- Komatsu Auto Idle Shutdown
- KOMTRAX® Level 5
- Lift cylinders and bucket cylinder
- Lights
  - Back-up light
  - Stop and tail light
  - Turn signal lamps, 2 front and 2 rear with hazard switch
  - Working lights, halogen, 2 front cab mount
  - Working lights, halogen, 2 front fender mount
  - Working lights, halogen, 2 rear grill mount
- Loader linkage with standard lift arm
- Multifunction mono-lever loader control with transmission F/R switch
- Parking brake, electric
- Radiator, wider core
- Radiator mask, swing up
- Rear view mirrors, outside (2) inside (2)
- Rims for 20.5-R25 tires
- ROPS/FOPS Cab Level 2
  - 2 x DC12V electrical outlets
  - Ashtray
  - Auto air conditioner
  - Cigarette lighter, 24V
  - Color LCD/TFT multi-monitor
  - Cup holder
  - Floor mat
  - Operator seat, reclining, air suspension type, heated
  - Radio, AM/FM with AUX input jack
  - Rear defroster, electric
  - Seatbelt, 2-point retractable, 76mm **3"** width
  - Space for lunch box
  - Steering wheel, tilt and telescopic
  - Sun visor, front window
  - Windshield washer and wiper, front with intermittent
  - Windshield washer and wiper, rear
- Service brakes, wet disc type
- Starting motor, 5.5 kW
- Transmission speed ranges, 4 forward and 4 reverse
- Vandalism protection kit, padlocks for battery box (2)

OPTIONAL EQUIPMENT

- Three-spool valve (will utilize integrated proportional control switch included in the multi-function mono-lever) and piping
- Auxiliary steering (SAE)
- Centrifugal engine air pre-cleaner
- Cutting edge (bolt-on type)
- Full rear fenders
- Limited slip differential (F&R)
- Quick coupler
- Various tire options, radial and bias
- Various bucket and fork options

AESS920-0326-V4
©2026 Komatsu America Corp.
AD12(Electronic View Only)

KOMATSU®

Note: All comparisons and claims of improved performance made herein are made with respect to the prior Komatsu model unless otherwise specifically stated.

www.komatsuamerica.com

Komatsu America Corp. is an authorized licensee of Komatsu Ltd.
Materials and specifications are subject to change without notice
KOMATSU®, Komatsu Care®, KOMTRAX® and KOMTRAX Plus® are registered trademarks of Komatsu Ltd.
All other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu America Corp. or their respective owners or licensees.