Specifications & Options

■ Standard ☑ Optional N/A Not Applicable

	Bobcat E45	
Engine	Standard	Long Arm
Emissions Tier (EPA)	Tier 4	Tier 4
Engine Fuel	Diesel	
Maximum Governed RPM	2,200 rpm	2,200 rpm
Horsepower	31.2 kW	31.2 kW
Turbocharged Engine	N/A	N/A
Performance		
Operating Weight	4571 kg	4787 kg
Weight Class	4.6 t	4.8 t
Travel Speed - High	4.2 km/h	4.2 km/h
Travel Speed - Low	2.4 km/h	2.4 km/h
Arm Digging Force	23,720 N	20,865 N
Bucket Digging Force	34,030 N	34,030 N
Boom Swing - Left	75°	
Boom Swing - Right	50°	
Maximum Dig Depth	3.3 m	3.6 m
Max Dump Height	3.6 m	3.8 m
Maximum Reach at Ground Level	5.8 m	6 m
Capacities		
Fuel Tank	79,9 l	
Hydraulic System		
Auxiliary Std Flow	75,7 l/min	
Auxiliary Pressure	210 bar	210 bar
Dimansion		
Length	5370 mm	5386 mm
Overall Length in Travel Position	5370 mm	5386 mm
Width	1960 mm	1960 mm
Height	2532 mm	2532 mm
Features		
Air Conditioning	N/A	N/A
Cab Enclosure	☑	☑
Cab Heater	☑	☑
Heater Air Conditioning	☑	☑
Radio	☑	☑
Tail Swing Type	Zero	Zero
Engine Shutdown	■	■
Auxiliary Hydraulics	■	■
Secondary Auxiliary Hydraulics	☑	☑
Quick Tach System	☑	☑
Rubber Track	■	■
Selectable Auxiliary Hydraulic Flow	■	■
Angle Blade	☑	☑

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.